

RESCO H₂Off Water-Based Paint Stripper and Cleaner

Technical Data Sheet

Description:

H₂Off is a water-based paint stripper and floor cleaner designed to remove multiple layers of coatings and paints from virtually all interior/exterior surfaces including:

- Oil-based paints
- Solvent-based paints
- Varnishes and waxes
- Certain plastic coatings

Applications:

H₂Off will effectively remove coatings from the following mediums:

- All metals (including soft metals)
- Brick
- Concrete

 Water-based paints & emulsions Polyurethanes Stains

Stone
Wood- hard woods and soft woods

 H_2Off can easily be applied by brush, roller or conventional airless sprayer. It is formulated to remain wet and effective over extended periods of time unlike most paint removal products.

H₂Off can also be use for the following applications:

- Graffiti Removal
- Ink Removal
- Hard Surface Cleaner/Degreaser

Special Benefits:

- Water-based
- Non-hazardous
- ☆ Biodegradable
- Non-caustic
- pH-neutral
- Chlorinated Solvent-free

- Paint system Cleaning
- Cure and Uncured Resin Removal
- Non-flammable
- Non-combustible
- Minimal evaporation.
- Minimal VOC content
- Non-irritant: does not cause skin burns

Corporate Office 100 Tony Holmes Drive P.O. Box 1667 Pelham, AL 35124 205-663-6350

Focus is the formula.

How to use:

First, test clean a small inconspicuous area. If no damage occurred in the test area, proceed with the rest of the cleaning. Dilute according to the table below. Dip or apply to surface to be cleaned and allow adequate time for chemical action. Rinse thoroughly with water. Since all cleaning jobs vary, try the leaner dilution first, then increase or repeat if necessary

Paint or Cured Resin Removal	Neat	(100%)
Floor cleaning or Graffiti Removal	3:1 to 1:1	(25%-50%)
Uncured Paint or Resin Removal	3:1 to 1:1	(25%-50%)
General Cleaning/Degreasing	10:1 to 5:1	(10%-20%)

Physical and Chemical Properties:

Appearance:	Clear liquid
Product Type:	Broad-purpose, water-based stripper/cleaner
Odor:	Sweet odor
pH, 5%	6.50
Specific Gravity:	1.0440
Lb/Gal:	8.70
Refractive Index @ 20 ⁰ C	1.3825
Solubility in Water:	Complete
Flash Point (TCC):	None

Example of H₂Off on Q-Panel:

- Enamel Paint
- Dipped in RESCO H₂Off for 30 minutes



Corporate Office 100 Tony Holmes Drive P.O. Box 1667 Pelham, AL 35124 205-663-6350